

TSS to assemble **DOEL** Brand Multimedia projectors.

DOEL

in technical collaboration with

Haier



T190

XGA DLP® Projector

Bright, Quiet, Lightweight

Vivid Presentation



- Texas Instruments DLP® Technology
- Latest generations single 0.55" XGA DMD Chip
- Brightness 3000 ANSI Lumens & contrast 2000:1
- Adopted 10bit High-End progressive chip from TI with perfect video scaling and excellent de-interlacing process.
- Vivid color by latest generation BrilliantColor™ II Technology and 6 segments color wheel.
- Individual color adjustment (R,G,B Gain/Bios)
- True-Vivid™ color turning Technology
- Capable with HDTV & Wide-Screen laptop signal
- High altitude setting
- Advanced security feature: Security bar and Kensington lock
- The capability of operating computer with remote control gives user more flexibility when delivering presentations.
- 3D Compatibility: supporting 120Hz playback



Specification	T190
Display Technology	Texas Instruments DLP® technology/ 0.55" XGA DMD Chip
Native Resolution	Native: 1024 x 768 (XGA) Support Computer signal up to UXGA (1600 x 1200) 60Hz
Brightness / Contrast Ratio	3000 ANSI Lumens / 2000 :1
Display Colors	1073.4 million colors (10bit)
Projection Lens	f = 21.95~24.18 mm; 1.1x manual zoom / focus lens.
Power Consumption	245W(MAX), <1W Standby
Image Size	30 to 300 inch
Focus	1.1x
Video Compatibility	HDTV (720p, 1080i/p), SDTV (480i/p, 576i/p) Full NTSC, PAL PAL-M, PAL-N, SECAM
Input / Output Connections	HDMI x 1 , VGA(VGA/YPbPr/ RGB) x 2, Monitor Output x 1, Composite Video x 1, Audio Input x 1, Audio output (Mini Jack) x 1, VGA Out x 1,RJ45 , mini USB (Software upgrade / Mouse control) x 1
Uniformity	85 %
Speaker	2W x 1
Noise	28 dB(Energy Saving Mode, 32 dB (Standard mode)
Lamp Type	180 watt user-replaceable lamp (UHP)
Lamp Life	4500 Hrs (Eco mode)/ 3000 Hrs(Standard mode)
Projection Screen	70" x 70" Tripod with Matte White
Presenter	Wireless Remote Control with Laser Pointer, Remotely control work up to 5 meters
Accessories	Original Carrying Bag, Power Cord, VGA Cable, user manual, warranty card
Certification	ISO9001: 2000
Power Supply	Universal AC 100 ~ 240V± 10%,50/60Hz
Dimensions(W x D x H)/ Weight	284 x 234.3 x 81.5 mm / 2.2kg (2.6 KGS)